

(12) **United States Patent**
Liu et al.

(10) **Patent No.:** **US 8,485,147 B2**
(45) **Date of Patent:** **Jul. 16, 2013**

(54) **IMPINGEMENT COOLING OF CYLINDERS
IN OPPOSED-PISTON ENGINES**

(75) Inventors: **Feng Song Liu**, San Diego, CA (US);
Jiongyang Wu, San Diego, CA (US);
Patrick R. Lee, San Diego, CA (US)

(73) Assignee: **Achates Power, Inc.**, San Diego, CA
(US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 111 days.

(21) Appl. No.: **13/136,402**

(22) Filed: **Jul. 29, 2011**

(65) **Prior Publication Data**

US 2013/0025548 A1 Jan. 31, 2013

(51) **Int. Cl.**
F02B 25/08 (2006.01)

(52) **U.S. Cl.**
USPC **123/51 B**

(58) **Field of Classification Search**
USPC 123/51 R, 51 B, 51 BA, 51 BD,
123/52.2

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,231,903 A 7/1917 Junkers
1,818,558 A 11/1929 Junkers
2,244,323 A * 6/1941 Antonsen et al. 123/41.78
2,412,952 A * 12/1946 Daub 123/51 BB

2,473,936 A * 6/1949 Burrough 123/45 R
2,998,808 A * 9/1961 Jackson 123/41.72
3,866,581 A * 2/1975 Herbert 123/51 B
5,058,536 A * 10/1991 Johnston 123/51 BA
6,182,619 B1 2/2001 Spitzer et al. 123/51 B
8,276,552 B2 * 10/2012 Lemke et al. 123/41.35
2009/0293820 A1 12/2009 Lemke et al. 123/41.35
2010/0212613 A1 8/2010 Lemke et al. 123/52.2
2010/0212637 A1 8/2010 Lemke et al. 123/51 R
2010/0212638 A1 8/2010 Rado et al. 123/51 R

* cited by examiner

Primary Examiner — M. McMahon

(74) *Attorney, Agent, or Firm* — Terrance A. Meador;
Incaplaw

(57) **ABSTRACT**

A cylinder cooling construction includes a cylinder liner with a sidewall, exhaust and intake ports opening through the sidewall, a bore, and a plurality of feed channels that are formed with and extend along the sidewall from a central band of the cylinder toward the exhaust and intake ports. A sleeve covering the sidewall includes a plurality of impingement jet ports that are arranged in at least one sequence extending around the central band and that are in liquid communication with the plurality of feed channels. An annular member disposed between the liner and the sleeve reinforces the central band. The sleeve further includes an inside surface with spaced-apart annular recesses that with the sidewall define liquid coolant reservoirs in the vicinity of the ports that are in liquid communication with the feed channels. Channels through bridges of exhaust port have first ends in liquid communication with the coolant reservoir in the vicinity of the exhaust port and second ends that open through a portion of an exhaust end of the cylinder.

23 Claims, 7 Drawing Sheets

